

23. (New) A clamping mechanism according to Claim 22 wherein the clamping mechanism further comprises a support member attached to said housing.

A2  
10077748.031502

24. (New) A clamping mechanism according to Claim 23 wherein the support member comprises a slide element, the slide element being slidably mounted on the housing, wherein the clamping arm is rotatably mounted on the slide element so that the sliding movement of the slide element and clamping arm guides the object held between the support member and the clamping arm.

25. (New) A clamping mechanism according to Claim 22 wherein the clamping arm is adapted to be mountable on a saw via a reversing slip clutch which allows the clamping arm to rotate in the reverse direction to the direction of free rotation of the rotary one way clutch if a reverse torque is exerted on the clamping arm which exceeds a specified threshold.

26. (New) A clamping mechanism according to Claim 25 wherein the one way rotary clutch and the reverse slip clutch are co-axially mounted.

27. (New) A clamping mechanism according to Claim 22 wherein the clamping arm is made from a plastics material having a metal weight located towards an end of the clamping arm distant from the one way rotary clutch.

28. (New) A clamping mechanism according to Claim 22, wherein the clamping arm has a holding surface and an end distant from the one way rotary clutch, the distant end having a curvature lying in a plane, so that the curvature direction of the clamping arm end is opposite to the curvature direction of the holding surface.

A2

1007718-021502